# tara<sup>™</sup> pure air<sup>®</sup> II bath

like the fabled Irish tower of kings that shares its name, the tara™ pure air® II bath is itself a singularly regal experience in an everyday world. I





Cozy up to the Tara<sup>™</sup> Pure Air<sup>®</sup> bath's corner configuration and linger as you massage away the cares of the day.

#### features:

- Exclusive 360° Balanced Airflow™ system
- 600 watt variable speed heated air blower
- Thermal Lumbar Comfort<sup>™</sup> (TLC)
- Timed purge cycle
- Safely use salts and aromatic oils
- PrO3™ Ozone Sanitation System standard

tara<sup>™</sup> pure air<sup>®</sup> II bath

model number: EB00 - RH

exterior dimensions:

60" long x 60" wide x  $20\frac{3}{4}$ " high

interior dimensions (at bottom):

45" long x 40" wide

operating gallons:

71 gallons





# Tara<sup>™</sup> Pure Air<sup>®</sup> II Bath

Model: EB00

# **Ordering Information**

Product Code: EB00 Tara™ Pure Air® II Bath Right Hand

- Center Drain Location
- Accessories / Hardware:

Trip-Lever Drain Kit #X559 Rotary Trip Kit, 26" Cable: #8730

• Trim Kit Finishes Available:

(827) - Chrome

(898) - Brushed Chrome

(815) - Satin Nickel

(829) - Bright Brass

(805) - Platinum

(826) - Brushed Nickel

(849) - Oil Rubbed Bronze

# Opt. Service Access 14" x 4" Service Access 27-1/4" 27-1/4" 35" 44"

## **Installation Notes**

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

# **Technical Specifications**

#### **Dimensions**

60" L x 60" L x 20-3/4" H (1524 mm) L x (1524 mm) L x (527 mm) H

#### Drain/Overflow

A: 16" (406 mm) B: 12-3/8" (314 mm)

#### Cutout

See Illustration Below

## **Total Weight**

1152 lb (523 kg)/ 46.1 lb/ft<sup>2</sup> (225 kg/m<sup>2</sup>)

# **Operating Gallonage**

71 U.S. Gal. (208 Liters) Min. 55 U.S. Gal. (208 Liters) Max. 87 U.S. Gal. (329 Liters)

# **Product Weight**

130 lb (59 kg)

## **Skirt Mounting**

Optional

#### **Electrical Specifications**

Requires a dedicated GFCI protected separate circuit.

Blower: 120 VAC, 15 AMP, 60 Hz.

#### Heater

No water heater is available on this unit. Blower has integral air heater.

